

XP 002153967

AN - 1986-004915 [25]

AP - JP19840090802 19840504

CPY - DAIM-N

DC - G03 P85

FS - CPI;GMPI

IC - C09J7/02 ; G09F3/02

MC - G03-B04

PA - (DAIM-N) DAIMATSU KAGAKU KOGYO KK

PN - JP60233178 A 19851119 DW198601 007pp

PR - JP19840090802 19840504

XA - C1986-002351

XIC - C09J-007/02 ; G09F-003/02

XP - N1986-003465

AB - J60233178 Material comprises (a) a surface substrate; (b) a first pressure sensitive adhesive layer (II) laminated to the face of (a); (c) a second pressure sensitive adhesive layer (III) laminated to (b); and (d) a release sheet tentatively adhered to (c).

- **USE/ADVANTAGE** - Used as label or sticker which is applied using the laminated adhesives. Since pressure sensitive adhesive layers have different properties and are laminated consecutively, the initial bond strength is retained sufficiently, and once it is adhered, it exhibits good adhesion durability with no squeeze out of adhesives. (II) contains pre-sure sensitive adhesive with relatively inferior adhesion but superior adhesion durability. (III) contains a pressure sensitive adhesive with relatively superior low temp. adhesion.

IW - ADHESIVE LABEL STICKER COMPRISE SUBSTRATE TWO PRESSURE SENSITIVE ADHESIVE LAYER RELEASE SHEET

IKW - ADHESIVE LABEL STICKER COMPRISE SUBSTRATE TWO PRESSURE SENSITIVE ADHESIVE LAYER RELEASE SHEET

NC - 001

OPD - 1984-05-04

ORD - 1985-11-19

PAW - (DAIM-N) DAIMATSU KAGAKU KOGYO KK

TI - Adhesive label or sticker - comprising substrate, two pressure sensitive adhesive layers and release sheet